



Materials:

18-8, type 304, 20 gauge (1.0mm) stainless steel with satin finish. Drawn, one-piece, seamless construction. Front of dispenser shall have same degree of arc as other General Partitions washroom accessories. Radius on corners and edges shall also compliment other General Partitions washroom accessories.

Operation:

Dispenser holds single or half-fold paper toilet seat covers. Dispenser fills from bottom through concealed opening. Capacity 250 toilet seat covers.

Installation:

Mount unit on wall or toilet compartment with two screws (not furnished) at points indicated by an S. For plaster or dry wall construction, provide concealed backing to comply with local building codes and secure with #8 x 1 1/2" (4.2 x 38mm) sheet metal screws. For other wall surfaces provide fiber plugs or expansion shields for use with sheet metal screws, or provide 1/8" (3mm) toggle bolts or expansion bolts.

Note: Provide 5" (125mm) minimum clearance from bottom of dispenser to top of any horizontal projection to provide room for filling dispenser from bottom.

Specification:

Surface mounted toilet seat cover dispenser shall be type 304, 20 gauge (0.9mm) stainless steel with drawn, one piece, seamless construction; exposed surfaces shall have satin finish. Front of toilet seat cover dispenser shall have same degree of arc and match other General Partitions washroom accessories in the washroom. Radius on corners and edges of toilet seat cover dispenser shall compliment other General Partitions washroom accessories. Unit shall have a rectangular opening for dispensing toilet seat covers and concealed opening in the bottom for filling. Capacity shall be 250 single or half-fold paper toilet seat covers.

Surface mounted toilet seat cover dispenser shall be model GP-109 from General Partitions Mfg., Corp. Erie, Pennsylvania