



Materials:

Cabinet —Type-304 stainless steel, 20 gauge, exposed surfaces have satin-finish.

Flange — Type-304 stainless steel, 20 gauge, exposed surfaces have satin-finish.

Waste Receptacle —Easy maintenance, removeable stainless steel waste receptacle locks into cabinet with a tumbler lock for security. Capacity: 12.5 Gal. Fabricated of type-304 stainless steel, 20 gauge, exposed surfaces have satin-finish.

Operation:

Waste receptacle is emptied manually on cycle determined by maintenance requirements. Disposable liner bags (by others) may be purchased to hang on internal hooks or may be draped over rim and held in place when receptacle is locked into cabinet. Keyed tumbler lock prevents unauthorized removal.

Installation:

Mount unit in wall recess using #10 self threading flat head screws (by others) through concealed mounting holes provided. For compliance with 2010 ADA Accessibility Standards. Install unit with top edge no higher than 48" (A.F.F.). Note that top of rough wall opening is 7/8" below top of unit.

Rough Wall Opening (RWO) required is 15 1/2" wide x 29" high x 4 1/4" minimum.

Specification:

Semi-recessed waste receptacle shall be type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish. Flange shall be drawn, one-piece, seamless construction. Bag holder shall have an arc at front and same shape as inside of waste receptacle area. Capacity of waste receptacle shall be 12.5 gal.

Semi-recessed waste receptacle shall be model GP-305 from General Partitions Mfg., Corp. Erie, Pennsylvania